

# Safety Data Sheet

Isopropanol 99%

## SECTION I - IDENTIFICATION

**SOLVENT DIRECT**

DATE PREPARED: ..... 9/8/1995

REVISION DATE: ..... 5/29/2014

CHEMTEL: ..... 800-255-3924

PRODUCT CODE: ..... IPA

ADDRESS: ..... 19129 S Hamilton Ave  
Gardena, CA 90248

EMERGENCY PHONE NUMBER: ..... (800) 255-3924

PRODUCT NAME: .....

CHEMICAL FAMILY: ..... Isopropanol 99%

CAS NUMBER: ..... 67-63-0

## SECTION II - HAZARDOUS IDENTIFICATION

### GHS CLASSIFICATION:

#### Classification

Flammable Liquids

Category 2

Serious Eye Damage/Eye Irritation

Category 2A

### DANGER!

#### GHS LABEL:



#### Hazard Statements

H225 Highly flammable gas and vapor

H319 Causes serious eye irritation

# Safety Data Sheet

## Isopropanol 99%

### Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P337+313	If eye irritation persists get medical advice/attention.
P370+378	In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+235	Store in a well ventilated place. Keep cool.
P501	Dispose of contents/container to an approved waste disposal plant.

### SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Isopropyl Alcohol	67-63-0	100%	400 ppm	200ppm (TWA)

### SECTION IV - FIRST AID MEASURES

**Contact with eyes:** Flush with water for 15 minutes. Seek immediate medical attention.

**Skin contact:** Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, seek immediate medical attention.

**Inhalation:** Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is affected or stopped. Seek immediate medical attention.

**Ingestion:** If swallowed. Do not induce vomiting. Seek immediate medical attention.

# Safety Data Sheet

## Isopropanol 99%

### SECTION V - FIREFIGHTING MEASURES

**Suitable Extinguishing Media:** Water fog, foam, CO2, dry chemical.

**Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

**Unusual Fire Fighting Hazards:** Product is flammable and may be ignited by heat, sparks, flames or other sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distances to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can explode in the heat of a fire.

### SECTION VI - ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Keep all sources of ignition and hot metal surfaces away from spill or release.  
Evacuate all unprotected personnel from the area.

**Environmental Precautions:** Prevent liquid from entering drains, sewers or waterways.  
Contain spill if it can be done with minimal risk.  
Notify proper authorities.

**Methods for Cleaning Up:** Use foam on spills to minimize vapors.  
Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.

### SECTION VII - HANDLING AND STORAGE

**Handling and Storage:**

- NFPA Class I storage.
- Vent container carefully before opening.
- Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
- "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

#### EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
Isopropyl Alcohol	67-63-0	400 ppm	200ppm (TWA)

## Safety Data Sheet

### Isopropanol 99%

**Engineering Controls:** Adequate local or mechanical ventilation to reduce vapor or mist to below the PEL or TLV.

**Monitoring:** Follow accepted work practices for handling a flammable material.  
Do not eat, drink or smoke in areas where this chemical is used or stored.  
Have eye wash stations and safety showers readily available.

#### Personal Protective Equipment (PPE)

**Eye Protection:** Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

**Skin Protection:** Impervious solvent resistant gloves.  
Impervious apron and work boots recommend where splashing may occur.

**Respiratory Protection:** Use the proper respirator in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

#### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, Colorless Liquid
Odor	Strong Alcohol Odor
pH@25°C	-
Melting/Freezing Point	-
Boiling Point	180°F
Flashpoint	53°F, TCC
Specific Gravity	0.784-.786
Solubility	Complete
Auto-Ignition Temperature	-
Decomposition Temperature	-
VOC Content	100% (6.50#/gal)
Odor Threshold	-
Boiling Range	180°F
Evaporation Point	2.4(Butyl Acetate=1)
Flammable Limits - Upper	12%
Flammable Limits - Lower	2%
Vapor Pressure	33 mmHg @ 20°F
Vapor Density (Air=1)	2.1 (Air=1)
Viscosity	-

#### SECTION X - STABILITY AND REACTIVITY

**Stability:** Stable

**Conditions to Avoid:** Extreme heat and ignition sources.

**Hazardous Decomposition/Byproducts:** Oxides of carbon and nitrogen under incomplete combustion conditions.

## Safety Data Sheet

Isopropanol 99%

**Hazardous Polymerization:** Will not occur.

**Polymerization Conditions to Avoid:** None

### SECTION XI - TOXICOLOGICAL INFORMATION

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

**Inhalation:** May cause irritation to the upper respiratory tract and CNS depression. Low to moderate degree of toxicity by inhalation.

**Eye Contact:** Causes eye irritation including stinging, watering and redness which may result in corneal injury.

**Skin Contact:** Contact may cause mild skin irritation including redness, burning and drying/cracking of the skin. No harmful effects from skin adsorption are expected.

**Ingestion:** Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema. Low degree of toxicity by ingestion.

#### Toxicity:

Component Name	LD50	LC50
2-Propanol	Oral - Rat - 5,045 mg/kg - Dermal - Rabbit - 12,800 mg/kg	Inhalation - Rat - 8 h - 16000 ppm
Isopropyl Alcohol	Oral - Rat - 5,045 mg/kg - Dermal - Rabbit - 12,800 mg/kg	Inhalation - Rat - 8 h - 16000 ppm

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

### SECTION XII - ECOLOGICAL INFORMATION

**Ecotoxicity:** Information not available.

**Mobility:** Information not available.

**Degradability:** Information not available.

**BioAccumulation:** Information not available.

# Safety Data Sheet

Isopropanol 99%

## SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Consult disposal expert. Can be disposed of by controlled incineration. Excessive quantities should not be permitted to enter drains, sewers, or water courses. Empty containers should be air dried before disposing.

## SECTION XIV - TRANSPORT INFORMATION

### DOT SHIPPING INFORMATION

Proper Shipping Name: Isopropanol

Contains:

Hazard Class and Label: 3

Identification Number: UN 1219

Packaging Group: II

Label Required:

## SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

### SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

### SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X	X	X		

### SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

### CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

## SECTION XVI - OTHER INFORMATION

HMIS Health: ..... 2

HMIS Flammability: ..... 3

HMIS Reactivity: ..... 0

Additional:

## Safety Data Sheet

Isopropanol 99%

### Specification Information

**Department issuing data sheet:** Compliance

**Email address:** compliance@transcheminc.com

**Training necessary:** Follow all local, state and federal regulations

### Intended Use of Product:

Seller and manufacturer disclaim any implied or expressed warranties, including warranties of merchantability or fitness of this product for any particular purpose. In no event shall seller be liable for any claim for incidental or consequential damages arising out of or in connection with the sale, delivery, transportation or use of this product. Seller's and manufacturer's liability in all events is limited to, and shall not exceed the purchase price paid for this product.